

Maint. Shop

SHERWIN-WILLIAMS CO/MARTIN SENOUR CO/ROGERS AUTO -- C-850 ACRYLIC LATEX CAULK -- 8030-01-145-0522

Various

=====  
Product Identification  
=====

Product ID:C-850 ACRYLIC LATEX CAULK  
MSDS Date:10/30/1996  
FSC:8030  
NIIN:01-145-0522  
MSDS Number: BWXTG  
==== Responsible Party ====  
Company Name:SHERWIN-WILLIAMS CO/MARTIN SENOUR CO/ROGERS AUTO  
Address:101 PROSPECT AVE N W  
City:CLEVELAND  
State:OH  
ZIP:44115-1042  
Country:US  
Info Phone Num:216-566-2902/216-566-2917  
Emergency Phone Num:216-566-2917/216-566-2902  
CAGE:54636

==== Contractor Identification ====

Company Name:SHERWIN-WILLIAMS CO THE  
Address:101 PROSPECT AVE NW  
Box:City:CLEVELAND  
State:OH  
ZIP:44115-1042  
Country:US  
Phone:800-251-2486/216-566-2242  
CAGE:54636

=====  
Composition/Information on Ingredients  
=====

Ingred Name:CARBONIC ACID, CALCIUM SALT (1:1), CALCIUM CARBONATE,  
DURAMITE \* 96-3 \*  
CAS:471-34-1  
RTECS #:FF9335000  
Fraction by Wt: 61%  
Other REC Limits:10 MG/CUM (DUST)

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:IRRITATION OF EYES, SKIN & UPPER  
RESPIRATORY SYSTEM. BURNING SENSATION.  
Explanation of Carcinogenicity:NONE  
Effects of Overexposure:IRRITATION, HEADACHE, NAUSEA, DIZZINESS,  
REDNESS, ITCHING, BURNING SENSATION.

=====  
First Aid Measures  
=====

First Aid:INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. KEEP WARM  
& QUIET. SKIN: WASH THOROUGHLY W/SOAP & WATER. EYES: FLUSH W/LARGE  
AMOUNTS OF WATER FOR 15 MINS OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====  
Fire Fighting Measures  
=====

Extinguishing Media:CO2, DRY CHEMICAL, ALCOHOL FOAM  
Fire Fighting Procedures:WEAR PROTECTIVE EQUIPMENT W/SCBA. WATER SPRAY

MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERRED.  
WATER MAY BE USED TO COOL CLOSED CONTAINERS.

Usual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE (DUE TO THE  
BUILDUP OF PRESSURE) WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE &  
REMOVE W/INERT ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE.  
USE ONLY W/ADEQUATE VENTILATION. TRANSFER ONLY TO APPROVED  
CONTAINERS W/COMPLETE & APPROPRIATE LABELING.

Other Precautions:KEEP OUT OF REACH OF CHILDREN. DON'T TAKE INTERNALLY.  
AVOID BREATHING VAPOR & SPRAY MIST. AVOID CONTACT W/SKIN & EYES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOSURE CAN'T BE CONTROLLED 1

Spec Gravity:1.67  
VOC Pounds/Gallon:26  
pH:7.9  
VOC Grams/Liter:.21  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Percent Volatiles by Volume:23

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
Stability Condition to Avoid:EXTREME HEAT & OTHER IGNITION SOURCES  
Hazardous Decomposition Products:BY FIRE: CO2, CO

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN APPROVED FACILITY. DON'T  
INCINERATE CLOSED CONTAINER. DISPOSE OF IN ACCORDANCE W/LOCAL,  
STATE & FEDERAL REGULATIONS.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.