



5-8-2018

Sharpening Stone Oil
By: NORTON

SHARPENING STONE OIL

MSDS Number

BZZTP

National Stock Number

5345-00N011469

Product Name

SHARPENING STONE OIL

Manufacturer

NORTON CO

Product Identification

Product ID: SHARPENING STONE OIL

MSDS Date: 03/01/1991

FSC: 5345

NIIN: 00N011469

MSDS Number: BZZTP

Responsible Party

NORTON CO

TROY, NY 12180

US

Emergency Phone: 518-266-2200

Info Phone: 518-266-2200

Preparer: J.J. MCG

Cage: NORTN

Contractor

NORTON CO, COATED ABRASIVE DIV

808

TROY, NY 12180

US

518-266-2200

Cage: 06565

Ingredients

MINERAL OIL, WHITE; (WHITE MINERAL OIL)

CAS: 64742-18-3

RTECS: PY8032000

OSHA PEL300 PPM

ACGIH TLV: 300 PPM

Hazards

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: INHALATION: NO APPLICABLE INFORMATION

FOUND BUT INHALING NOT RECOMMENDED. INGESTION: NO APPLICABLE

INFORMATION FOUND BUT INGESTION NOT RECOMMENDED. SKIN: GENERALLY

INNOCUOUS, BUT PROLONGED CONTACT WITH SKIN MAY EVENTUALLY LEAD TO

EXTRACTION OF NATURAL OIL WITH RESULTANT IRRITATION.

Explanation of Carcinogenicity: NOT RELEVANT



Effects of Overexposure:SEE HEALTH HAZARDS.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:INHALATION: GET MEDICAL ASSISTANCE IF NECESSARY. INGESTION:
DO NOT INDUCE VOMITING; CALL MD. SKIN: OBTAIN FIRST AID OR MEDICAL
ASSISTANCE IF NEEDED. WASH SKIN WITH SOAP AND WATER. EYES: FLUSH
EYES WITH WATER FOR AT LEAST 15 MINUTES.

Fire Fighting

Flash Point Method:COC
Flash Point:350F,177C
Lower Limits:1%
Upper Limits:5.5%
Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY OR
FOG.
Fire Fighting Procedures:USE NIOSH APPROVED SCBA AND FULL PROTECTIVE
EQUIPMENT .
Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS.

Accidental Release

Spill Release Procedures:RECOVER FREE LIQUID. ADD ABSORBENT TO SPILL
AREA. KEEP PETROLEUM PRODUCTS OUT OF STREAMS AND WATERWAYS.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions:KEEP CONTAINERS CLOSED. KEEP AWAY FROM
HEAT AND OPEN FLAME.
Other Precautions:NO APPLICABLE INFORMATION FOUND.

Exposure Controls

Respiratory Protection:NORMALLY NOT NEEDED. USE NIOSH APPROVED
RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .
Ventilation:NORMALLY NOT NEEDED.
Protective Gloves:IMPERVIOUS GLOVES .
Eye Protection:ANSI APPROVED CHEM WORKERS GOGGLES .
Other Protective Equipment:ANSI APPROVED EYE WASH & DELUGE SHOWER .
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
VP: -2X10(3) @ 100F.

Chemical Properties

Boiling Pt:B.P. Text:>590F,>310C
Vapor Pres:SUPDAT
Vapor Density:10
Spec Gravity:0.867
Evaporation Rate & Reference:0.01
Solubility in Water:NEGLIGIBLE
Appearance and Odor:CLEAR, TRANSPARENT, WATER WHITE LIQUID; ODORLESS.
Percent Volatiles by Volume:NEGLIG

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS LIKE LIQUID CHLORINE AND CONCENTRATED OXYGEN.
Stability Condition to Avoid:NO APPLICABLE INFORMATION FOUND.
Hazardous Decomposition Products:CARBON DIOXIDE IN THE CASE OF
INCOMPLETE COMBUSTION.

Disposal

Waste Disposal Methods:DISPOSAL MUST BE IN ACCORDANCE WITH FEDERAL,
STATE AND LOCAL REGULATIONS . INCINERATE ABSORBED MATERIAL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this



document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.